
VEGA B Light II





VEGA B LIGHT IIMESH PANELS

Intended use: VEGA B Light II mesh panels are a universal solution that can be used both in industrial and residential areas. The mesh panels are installed around residential houses, parks, gardens, public utility buildings, playgrounds, as well as around factories, various sorts of storage and warehouse areas.

PROVEN TECHNOLOGY

The VEGA B Light II panel is welded using raw wire, next it is hot-dip galvanized or electrogalvanized and then powder coated. Special features of the panel manufactured using this technology include reliable welds and the elimination of possible corrosion centres.

RESISTANT TO CORROSION

Mesh panels are subjected to strict testing in our in-house laboratory which checks the product's corrosion-resistance. This allows us to offer a product with excellent quality parameters.

UNIVERSAL INSTALLATION

VEGA B Light II panels can be mounted on 4 types of posts using 6 types of fixing accessories available from WIŚNIOWSKI.

PART OF A SYSTEM

The VEGA B Light II mesh panel is an integral part of the fence. It can be installed as part of a system together with the sliding gate or a gate and wicket from the WIŚNIOWSKI range.



Product description

General description

VEGA B Light II panels belong to the 3D panel group. Embossing is a distinctive feature of this product group. Embossing adds extra rigidity to panels. The number of embossed elements depends on the panel height.

Area of application

VEGA B Light II mesh panels are a universal solution that can be used both in industrial and residential areas. The mesh panels are installed around residential houses, parks, gardens, public utility buildings, playgrounds, as well as around factories, various sorts of storage and warehouse areas.

Technical data


Panels

VEGA B Light II panels are spot welded using single steel bars. VEGA B Light II panels are terminated with extended 30 [mm] long bars on one end, in the bottom or top section of the fence.



VEGA B Light II panel available heights

Wire gauge of the hot-dip galvanized panel Wire gauge of the DUPLEX system panel Straight mesh size Small mesh size Panel width 3.0 [mm] 3.0 [mm] 80x100 [mm] 80x50 [mm] 2,500 [mm]



1,530 mm



Post - installation methods

VEGA B Light II panels can be mounted on 4 types of posts using 6 types of fixing accessories available from WIŚNIOWSKI. The panels can be installed in a flat or inclined area, directly above the ground or using a concrete plank. Posts can be installed directly in the ground or on a concrete foundation using base plates.



Galvanized sheet profile post coated with polyester paint. A proprietary solution by

WIŚNIOWSKI

Post cross-section 65x42 [mm].

The post is supplied with a plastic cap and holes for easy installation.

Corrosion protection:

 galvanizing + polyester coating.
Available colours: RAL 6005, grey similar to RAL 7016.

Accessories: The panels are installed using accessories including: dedicated plastic mounting clips for VEGA B Light panels (for 4 [mm] wire gauge), M6 hex screws, washers, M6 nuts, plastic caps).



Round post.

Post diameter 40 [mm].

The post is supplied with a plastic cap and holes for easy installation.

Corrosion protection:

- · hot-dip galvanizing,
- galvanizing + polyester coating.

Accessories: Panels are mounted on posts using round steel clamps. Clamps are available in galvanized and galvanized + polyester coating versions. Accessories include: metal clamp; dedicated plastic clips for VEGA B Light panels (up to 4 [mm] wire gauge), M8x25 [mm] stainless steel screws, stainless steel washers, M8 stainless steel shear nuts. Fixing clamps are available in middle, corner, and end versions.



Round post.

Post diameter 48.3 [mm].


The post is supplied with a plastic cap and holes for easy installation.

Corrosion protection:

- · hot-dip galvanizing,
- galvanizing + polyester coating.

Accessories: Panels are mounted to posts using round clamps.

Accessories include: metal clamp; plastic clips for 4 [mm] wire gauge, M8x25 [mm] stainless steel screws, stainless steel washers, M8 stainless steel shear nuts. Fixing clamps are available in middle, corner, and end versions.



Post made of a 60x40x1.5 [mm] section.

The post is supplied with a plastic cap, holes for simple installation, and a standard clamp.

Corrosion protection:

- · hot-dip galvanizing,
- galvanizing + polyester coating.

Accessories: Panels are mounted on posts using rectangular steel clamps. Clamps are available in galvanized and galvanized + polyester coating versions. Accessories include: metal clamp; dedicated plastic clips for VEGA B Light panels (up to 4 [mm] wire gauge), M8x25 [mm] stainless steel screws, stainless steel washers, M8 stainless steel shear nuts. Fixing clamps are available in middle, corner, and end versions.



Post made of a 60x40x1.5 [mm] section.

The post is supplied with a plastic cap, holes for simple installation, and a D1 clamp.

Corrosion protection:

- hot-dip galvanizing,
- galvanizing + polyester coating.

Accessories: Panels are mounted to posts using OMEGA D1 clamps. Clips are made of high quality PA 6 polyamide, while clamps are made of lnox M6 stainless steel. The set includes two nuts and two plastic caps. Clamps have a universal colour and can be used with middle posts, corner posts, and end posts.



Post made of a 60x40x1.5 [mm] section.


The post is supplied with a plastic cap, holes for simple installation, and a D2 clamp.

Corrosion protection:

- · hot-dip galvanizing,
- galvanizing + polyester coating.

Accessories: Panels are mounted to posts using OMEGA D2 clamps. Clamps are made of high quality PA 6 polyamide, while the fastening element is made of lnox M6 stainless steel. The set includes two nuts and two plastic caps. Clamps have a universal colour and can be used with middle posts, corner posts, and end posts.





VEGA B Light II panel installation options

VEGA B Light II MESH PANEL										
Fence height [mm]	Panels width x height [mm]	Number of profile recesses on the panel	Post GAMMA		Post OMEGA, OMEGA D1 OMEGA D2		Post OMEGA 40		Post OMEGA 48	
			Quantity of accessories	Post length	Quantity of clamps	Post length	Quantity of clamps	Post length	Quantity of clamps	Post length
1,600	2,500x1,530	3	3	2,000 2,400*	3	2,000	3	2,000	3	2,000

^{*) -} Recommended post height when posts are set in the ground using a concrete plank.

Mesh panel manufacturing and coating technology

Mesh panels are welded using raw wire. The panels are manufactured in accordance with the PN-EN 10223-7:2013-05 standard. The mesh panel can be protected from corrosion by hot-dip galvanizing (in accordance with EN ISO 1461:2000) or electrogalvanizing (in accordance with PN EN ISO 2081:2011) and polyester coating (in accordance with EN 10244-2:2010). The combination of the zinc and varnish coatings in the DUPLEX system substantially contributes to extending the life of WIŚNIOWSKI fences. We offer 10 year anti-corrosion guarantee on our coated panels.







Not available.

Build an extensive industrial fencing system



The WIŚNIOWSKI fences are a system of solutions ensuring comprehensive protection for your property. Our residential and industrial product range includes modern steel, profile, and panel fences. Reliable, high quality, and durable, our fences also boast elegant and stylish look. WIŚNIOWSKI's comprehensive offer makes closing off your property simple and reflects great care for safety, security, and appearance. Take advantage of our complete range and build your own fencing.







WIŚNIOWSKI Sp. z o.o. S.K.A. PL 33-311 Wielogłowy 153 tel. +48 18 44 77 111 Fax +48 18 44 77 110

www.wisniowski.eu

Let us inspire you! See other solutions from WIŚNIOWSKI!

The products shown in the pictures often feature special accessories and do not always correspond to their standard versions • The technical data sheet does not constitute an offer within the meaning of the Polish Civil Code • The manufacturer reserves the right to introduce changes without notice • NOTE: The colours shown in the technical data sheet are for reference only • All rights reserved • Copying and use, in part or in full, is prohibited without the consent of WIŚNIOWSKI Sp. z o.o. S.K.A. • VEGA B Light II/10.23/EN